



9	BLACK HEAT SHRINK TUBE $\phi 1.5 \times 25\text{mm}$	4
8	BLACK HEAT SHRINK TUBE $\phi 7.0 \times 20\text{mm}$	2
7	BLACK HEAT SHRINK TUBE $\phi 1.0 \times 8\text{mm}$	2
	MOLDED PE COLOR TRANSPARENT	
6	MOLDED PVC BLACK	
	BRACKET WITH TWO HOLE FOR 1394 6P FEMALE	1
5	UL20276 IEEE1394 CABLE, 2 TWISTED PAIRS 28AWG AND 2C 22AWG, OD 6.0mm, JACKET BLACK	320mm*2
4	HEX-NUT #4-40, 5*7.7mm	4
3	SCREW #4-40, 5.5*8mm	4
2	TERMINLA: CKM2542-T	16
	HOUSING: CKM2542-2*5P, PITCH 2.54mm	2
1	IEEE1394 6P FEMALE, GOLD FLASH ON CONTACTS, BLACK INSULATOR	2
No.	DESCRIPTION	QTY



CHECKED	APPROVED	SCALE: 1:2	REV NO	DATE	DESCRIPTION	BY	CHECKED	TOLERANCE UNLESS NOTED
JOJO		UNIT: mm(in)	A					.0 $\pm 0.30(0.12)$
DRAWN NAME	DATE	CAD NO	B					.00 $\pm 0.20(0.08)$
ANDY	08.08.06	821040	C					.000 $\pm 0.10(0.04)$
PROJECTION:								

DWG NAME 821040 (RoES)