



## Configuration Description

Configured KISS 2U MB System  
 1 EXT 5.25", 1 Bottom Front Accessible & 1 INT 3.5" Drive Bay  
 2 Full Size Cards, 2U x 19" W x 18.58" L  
 3 SATA DEVICES MAX FOR ENTIRE SYSTEM

Categories	QTY	Select one each category
<b>POWER SUPPLIES</b>		
		602-0132-00 KIT 300W P/S KISS
		602-0133-00 KIT 460W P/S KISS
<b>CPU</b>		
		3-274953-0 Intel Core 2 Quad Desktop Q9400 2.66GHz FSB1333 6MB
		3-274951-0 Intel Core 2 Duo Desktop E8400 3.00GHz FSB 1333 6MB
		3-274950-0 Intel Core 2 Duo Desktop E7400 2.80GHz FSB1066 3MB
<b>MEMORY</b>		
		4096N-DDR3-1333 x2 8GB DDR3-1333 NON-ECC DIMM (4096x2)
		2048N DDR3-1333 x4 8GB DDR3 UNB Non-ECC DIMM (2048x4)
		2048N DDR3-1333 x2 4GB DDR3 UNB Non-ECC DIMM (2048x2)
		1024N DDR3-1333 x2 2GB DDR3 UNB Non-ECC DIMM (1024x2)
<b>DRIVE BAY 1</b>		
External 5.25" Drive Bay		NO
		602-0142-00 KIT SATA-300 1TB W/CARRIER
		602-0135-01 KIT SATA-500GB W/CARRIER
		IHAS324 DVD +/-RW/R 24X-SATA
<b>DRIVE BAY 2</b>		
Bottom Front Accessible Drive Bay		NO
		ST1000DM003 3.5" 1TB 7200RPM 64MB 4K SATA HDD
		ST500DM002 3.5" 500GB 7200RPM 16MB 4K SATA HDD
		602-0152-00 KIT SL-DVDRW SATA & DATA/PWR CABLE
<b>DRIVE BAY 3</b>		
Internal 3.5" Drive bay		NO
		ST1000DM003 3.5" 1TB 7200RPM 64MB 4K SATA HDD
		ST500DM002 3.5" 500GB 7200RPM 16MB 4K SATA HDD
<b>VIDEO CARDS</b>		
		NO
		PCIE-220GT1GB PCIE X16 NVIDIA 220GT 1GB
		G450-PCI++ MATROX G450 PCI 32MB DUAL VIDEO CARD
<b>ETHERNET</b>		
		NO
		PCIE-EXPI9301CT PCIE 10/100/1000 SINGLE INTEL NIC RJ45
		ETHER-100TX+ ENET NIC 10/100 PCI RJ-45
<b>SOUND CARDS</b>		
		NO
		SBAUDIGY-SE 24BIT/96KHZ PCI SOUND CARD RHS
<b>I/O Cards</b>		
		NO
		PCIE-F5U602 3X1394 3XUSB2.0 PCIE X1 ROHS
<b>OPERATING SYSTEM</b>		
		NO
		WIN7-PRO32SP1 MS WINDOWS PRO 32-BIT OEM SP1
		WIN7-PRO64SP1 MS WINDOWS PRO 64-BIT OEM SP1
		WINXPPROFES WINDOWS XP PRO FOR EMB SYSTEMS SP2C
<b>OPTION KIT</b>		
		NO
		602-0215-00 KIT 1 PCIe x16 RISER EXPANSION
		602-0216-00 KIT 1 PCI 32 BIT+PCIe x16 RISER EXPANSION
		602-0217-00 KIT 1 PCIe x4+1 PCIe x16 RISER EXPANSION
		602-0218-00 KIT 2 PCI 32 BIT RISER EXPANSION
<b>SPECIAL I/O CARDS</b>		
		NO
		P/N DESCRIPTION
<b>SPECIAL INTEGRATION</b>		
		NO
		8GB memory requires use of a 64-bit OS (not WINXP 32-bit compatible)
		DESCRIBE/COMMENTS/INFO/INSTRUCTIONS/SPECS/ETC

All rights reserved. No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), without the express written permission of Kontron America.

All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Kontron and the Kontron logo are registered trademarks of Kontron AG. All other brand or product names are trademarks or registered trademarks or copyrights by their respective owners and are recognized.